

Weigh feeder FK-5

Weigh feeder for flow control



- Feed out and flow rate control of granules or powder from storage bins, silos and other containers to process systems.
- Capacity from 150 to 10000 litres/hour.
- Stand alone or PC-surveillance for flow control or ratio control when using S-E-G belt weighing instruments.
- Unique design giving high accuracy with easy cleaning and maintenance.
- Enclosed versions and stainless steel versions as options.

The feeder operates according to a revolutionary principle. The material is pulled out of the hopper and pushed over the weighing area. The drive consists of two teathed wheels placed between the hopper and the weigh area.

The wheels drive the conveyor through slots in the belt, ensuring minimal tension at the weigh area and preventing sideways movement of the belt, eliminating most of the possible weighing errors.

General data

Belt width:	Effective: 460mm.
Belt type:	Polyester fibre with PVC or urethane layer. Food quality.
Load sensor:	S-E-G loadcell KN-15 IP 67 (To be ordered separately, see spec. F31-16E).
Belt speed sensor:	S-E-G tachometer type F.
Belt cleaning:	Plow scraper on both sides of belt at the feed end.
Maintenance:	The feeder is placed on slide rails to enable it to be easily removed for maintenance.
Drive:	3PH 220/380 V 120 W, IP54, spur gear.
Accuracy:	Typically: 0.1 to 0.5 % of maximum capacity.

